(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property **Organization**

International Bureau





(43) International Publication Date 4 November 2004 (04.11.2004)

PCT

(10) International Publication Number WO 2004/095500 A2

(51) International Patent Classification⁷:

H01J 37/00

(21) International Application Number:

PCT/US2004/011553

15 April 2004 (15.04.2004) (22) International Filing Date:

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 10/419,035

US 18 April 2003 (18.04.2003)

- (71) Applicant (for all designated States except US): IMAGO SCIENTIFIC INSTRUMENTS [US/US]; 6300 Enterprise Lane, Madison, WI 53719 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): STRAIT, David, Robert [US/US]; 5907 Shumann Drive, Madison, WI 53711 (US).
- (74) Agents: FIESCHKO, Craig, A. et al.; DeWitt Ross & Stevens S.C., Suite 401, 8000 Excelsior Drive, Madison, WI 53717-1914 (US).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: VACUUM CHAMBER WITH RECESSED VIEWING TUBE AND IMAGING DEVICE SITUATED THEREIN



(57) Abstract: A vacuum chamber includes chamber walls separating a chamber interior and a chamber exterior, with one or more access ports defined in the chamber walls. A viewing tube extends from the chamber exterior into the chamber interior and terminates in a window. A positioner for imaging devices is then provided within the viewing tube, and is thus situated at least partially within the chamber interior with its imaging device(s) oriented towards the window of the viewing tube to allow imaging of areas within the vacuum chamber. The positioner preferably allows translation and/or rotation of an imaging device within the viewing tube within two perpendicular planes oriented along the axis of the viewing tube, thereby allowing the imaging device to view an area of interest from more angles oriented about the area of interest than would otherwise be possible if the imaging device was situated outside the vacuum chamber.

